



T-Cover-Profil Nr. 741, 25 mm

- Edelstahl, 1.4301 (V2A).
- Für Holzfußböden, Kermische Fliesen und Steinböden.

Werkstoff: 1.4301 (DIN EN 10088-2)
Nicht genormte Bezeichnung: Edelstahl rostfrei, V2A

Geeignet für: Fertigparkett, Massivholzböden, Keramische Fliese / Steinböden
Montageart: Kleben

T-Cover-Profile sind für die flexible Verbindung gleich hoher Bodenbeläge geeignet.
Sie werden insbesondere für verklebte Böden wie zum Beispiel bei Parkett oder auf keramischen Fliesen eingesetzt.
Der senkrechte Steg wird in die mit Silikon gefüllte Fuge eingelegt.
Somit können T-Cover-Profile auch problemlos nachträglich verlegt werden.



T-Cover-profile no. 741, 25 mm

- Stainless steel, 1.4301 (V2A).
- For wooden floors, ceramic tiles and stone floors.

Material: 1.4301 (DIN EN 10088-2)
Non-standardised description: Stainless steel, V2A

Suitable for: Finished parquet, Massive wooden flooring, Ceramic tiles / Stone floorings
Installation: gluing

T-Cover sections are suitable for the flexible connection of equally high floor coverings.
They are used in particular for bonded floors such as parquet or ceramic tiles.
The vertical strip is inserted into the silicone-filled joint. This means that T-Cover profiles can also be installed subsequently without any problems.