



Winkelprofil Nr. 160, 24,5 x 10 mm

- Aluminium.
- Selbstklebend.

TÜV Zertifikat-Nr. 44 780 14206214

Werkstoff:	EN AW 6063 (DIN EN 573)
Werkstoffzustand:	T6 (DIN EN 755-2)
Vorbehandlung:	E6 (DIN EN 17 611)
Schichtdicke Eloxal:	Klasse 15 (DIN EN 17 611)
Pulverbeschichtung:	optional (RAL/Metallic/Holzdekor)

Klebstoff:	Schmelzhaftklebstoff (synthetische Kautschukbasis)
Viskosität:	10.000 +/- 3.000 mPa.s (170°C)
(Brookfield RVT DV-II, Sp 27 ASTM D 3236)	
FDA Status:	gemäß § 175.105 Adhesives
Transportschutz:	abgedeckt mit Silikonpapier

Geeignet für: Designbelag / LVT Click und Loose Lay, Designbelag / LVT Dryback, Laminat / Multilayer
Montageart: Kleben

Winkelprofile sind ideal geeignet als kleiner Treppenwinkel, als Türschwellenprofil oder als Abschluss an Podesten.
Sie schützen die Kanten des Bodenbelags dauerhaft.



Angle edge no. 160, 24.5 x 10 mm

- Aluminium.
- Auto-adhesive.

TÜV certification no. 44 780 14206214

Material:	EN AW 6063 (DIN EN 573)
Material condition:	T6 (DIN EN 755-2)
Pre-treatment:	E6 (DIN EN 17 611)
Thickness of anodised layer:	Class 15 (DIN EN 17 611)
Powdercoating:	optional (RAL/metallic/woodstyle)

Adhesive:	hotmelt adhesive (synthetic rubber-based)
Viscosity:	10.000 +/- 3.000 mPa.s (170°C)
(Brookfield RVT DV-II, Sp 27 ASTM D 3236)	
FDA state:	acc. to § 175.105 Adhesives
Protection:	covered with silicone paper

Suitable for: Design flooring / LVT click and loose lay, Design flooring / LVT dryback, Laminat / multilayer
Installation: gluing

Angle edges are ideally suited as a small staircase angle, as a door threshold profile or as a termination on platforms.
They protect the edges of the flooring permanently.