



Winkelprofil Nr. 292, 20 x 10 mm

- Aluminium.
- Ungelocht.
- Auf Anfrage biegbar.

Werkstoff:	EN AW 6063 (DIN EN 573)
Werkstoffzustand:	T6 (DIN EN 755-2)
Vorbehandlung:	E6 (DIN EN 17 611)
Schichtdicke Eloxal:	Klasse 15 (DIN EN 17 611)

Geeignet für: Designbelag / LVT Click und Loose Lay, Designbelag / LVT Dryback, Textile und elastische Bodenbeläge, Laminat / Multilayer

Montageart: Kleben, Schrauben

Winkelprofile sind ideal geeignet als kleiner Treppenwinkel, als Türschwellenprofil oder als Abschluss an Podesten. Sie schützen die Kanten des Bodenbelags dauerhaft.



Angle edge no. 292, 20 x 10 mm

- Aluminium.
- Without screw holes.
- Bendable on request.

Material:	EN AW 6063 (DIN EN 573)
Material condition:	T6 (DIN EN 755-2)
Pre-treatment:	E6 (DIN EN 17 611)
Thickness of anodised layer:	Class 15 (DIN EN 17 611)

Suitable for: Design flooring / LVT click and loose lay, Design flooring / LVT dryback, Textile and elastic floor coverings, Laminate / multilayer

Installation: gluing, screwing

Angle edges are ideally suited as a small staircase angle, as a door threshold profile or as a termination on platforms. They protect the edges of the flooring permanently.