



Spannteppich-Abschlussprofil Nr. 342, 35,5 x 11,2 mm

- Aluminium.
- Für textile Beläge bis 7 mm.
- Mit Krallenhaken für Spannteppiche.

Werkstoff: EN AW 6063 (DIN EN 573)
Werkstoffzustand: T6 (DIN EN 755-2)
Vorbehandlung: E6 (DIN EN 17 611)
Schichtdicke Eloxal: Klasse 15 (DIN EN 17 611)

Zubehör: Befestigungsmaterial.
Geeignet für: Textile und elastische Bodenbeläge
Montageart: Schrauben

Universalabschlussprofile sind für verschiedene Bodenbeläge, von nur 2 mm dünnen Designböden bis hin zu 22 mm starken Massivholzdielen, erhältlich und universell einsetzbar. Sie sorgen für einen sauberen Abschluss und schützen Kanten dauerhaft.



Border section for wall-to-wall-carpet no. 342, 35.5 x 11.2 mm

- Aluminium.
- For textile floor coverings up to 7 mm.
- With claw hooks for clamping carpet.

Material: EN AW 6063 (DIN EN 573)
Material condition: T6 (DIN EN 755-2)
Pre-treatment: E6 (DIN EN 17 611)
Thickness of anodised layer: Class 15 (DIN EN 17 611)

Accessories: Fastening material.
Suitable for: Textile and elastic floor coverings
Installation: screwing

Universal edge sections are available for various floor coverings. They can be used with only 2 mm thin design floorings up to 22 mm thick solid wood flooring. They provide a clean finish and ensure a long lasting edge protection for the floor covering.